NSN 5905-00-950-0040

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-950-0040

Electrical Resistance: 1.780 kilohms Resistance Tolerance In Percent: 0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In
Resistance Tolerance In Percent: 0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: 0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Not established Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Body Diameter: 0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
0.187 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.500 free air
0.625 inches Power Dissipation Rating In Watts: 0.500 free air
Power Dissipation Rating In Watts: 0.500 free air
0.500 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/2 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0