NSN 5905-00-950-0208

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-950-0208

Electrical Resistance: 732.000 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Inclusure Range Of Tempurature Coefficient In Deg Celsius: 55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0/165.0 Tempurature Range Of Tempurature Coefficient In Deg
Resistance Tolerance In Percent: 1.1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Inferpurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+165.0 Inclosure Method: Encapsulated Inferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.109 inches Body Length: 10.250 inches Power Dissipation Rating In Watts: 10.125 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+165.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Wire lead Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Reliability Indicator: Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Not established Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator:
Power Dissipation Rating In Watts: 0.125 free air Style Designator:
0.125 free air Style Designator:
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/7 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0