NSN 5905-00-950-7246

Precision Wire Wound Variable Resistor - Page 1 of 2



-7246

View Online at https://aerobasegroup.com/nsn/5905-00-950-
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.9360 inches and 1.9370 inches
Pilot Length:
Between 0.0290 inches and 0.0320 inches
Overall Length:
Between 1.217 inches and 1.260 inches
Undercut Diameter:
Between 1.9375 inches and 1.9385 inches
Undercut Width:
Between 0.0700 inches and 0.0900 inches
Body Diameter:
Between 2.099 inches and 2.151 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.198 inches and 0.218 inches
Body Length:
Between 0.990 inches and 1.010 inches
Overall Diameter:
Between 2.099 inches and 2.151 inches
Mounting Lip Diameter:
Between 1.9900 inches and 2.0100 inches
Mounting Lip Depth:
Between 0.0680 inches and 0.0850 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 319.0 and 321.0
Maximum Starting Torque:
0.60 inch-ounces
Shaft End Play:

Shaft End Play: 0.006 inches

NSN 5905-00-950-7246

No **Fiig:**

Precision Wire Wound Variable Resistor - Page 2 of 2

