NSN 5905-00-950-7406

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-950-7406

Section Oceantitus
Section Quantity:
1 Partic Studen
Body Style:
Cylindrical Political Indicators
Reliability Indicator:
Not established
Overall Length:
0.672 inches
Body Diameter:
0.938 inches
Body Length:
0.453 inches
Overall Diameter:
1.375 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.438 inches
Terminal Location:
Front end
Mounting Method:
Tab
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-1000.0/+1000.0 single section
Power Dissipation Rating Per Section In Watts:
0.167 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55 0 single section

55.0 single section

NSN 5905-00-950-7406

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0