## NSN 5905-00-950-7660

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-950-7660

**Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.4365 inches and 0.4370 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Overall Length:** Between 1.047 inches and 1.057 inches **Undercut Diameter:** Between 0.4365 inches and 0.437 inches **Undercut Width:** Between 0.0570 inches and 0.0670 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** Between 0.1243 inches and 0.1245 inches **Shaft Length:** 0.250 inches **Body Length:** Any acceptable **Overall Diameter:** 0.500 inches **Mounting Lip Diameter:** 0.5000 inches **Mounting Lip Depth:** Between 0.6410 inches and 0.6510 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 287.0 and 297.0

**Maximum Starting Torque:** 

1.50 inch-ounces

**Maximum Running Torque:** 

0.75 inch-ounces

NSN 5905-00-950-7660 Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.006 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:

## NSN 5905-00-950-7660

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0