NSN 5905-00-950-8211

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-950-8211
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-260.0/+260.0 first temp coefficient
Electrical Resistance:
150.000 ohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0 temp range of first temp coefficient
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reactance Characteristic:
Inductive
Reliability Indicator:
Not established
Terminal Length:
0.531 inches
Body Length:
3.500 inches
Body Width:
1.187 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.250 inches
Power Dissipation Rating In Watts:
53.000 free air
Terminal Width:
0.265 inches
Mounting Hole Size:
0.196 inches
Style Designator:
Terminals one edge
Test Data Document:
81349-mil-r-26/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a

-

Unit Of Measure:

NSN 5905-00-950-8211

Inductive Wire Wound Fixed Resistor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	\sim	n	
$\boldsymbol{-}$	CIII		ıιa	114	.aı	ı		

No

Fiig:

A001a0