## NSN 5905-00-951-1425

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



-951-1425

| View Online at https://aerobasegroup.com/nsn/5905-00- |
|---|
| Section Quantity:                                     |
| Body Style:   |
| Rectangular w/mounting holes/slots                    |
| Reliability Indicator:                                |
| Not established                                       |
| Overall Length:                                       |
| Between 1.281 inches and 1.345 inches                 |
| Terminal Length:                                      |
| Between 0.486 inches and 0.516 inches                 |
| Overall Height:                                       |
| Between 0.780 inches and 0.844 inches                 |
| Overall Width:  |
| Between 0.270 inches and 0.290 inches                 |
| Mounting Hole Diameter:                               |
| 0.086 inches  |
| Shaft Diameter:                                       |
| 0.125 inches  |
| Shaft Length:   |
| Between 0.047 inches and 0.079 inches                 |
| Body Length:  |
| Between 1.234 inches and 1.266 inches                 |
| Body Width:   |
| Between 0.270 inches and 0.290 inches                 |
| Body Height:  |
| Between 0.296 inches and 0.328 inches                 |
| Shaft Style:  |
| Round, slotted  |
| Shaft Bearing Type:                                   |
| Bearing   |
| Actuator Type:  |
| Single shaft  |
| Center To Center Distance Between Terminals:          |
| 0.700 inches  |
| Lateral Distance Between Mounting Hole Centers:       |
| Between 0.995 inches and 1.005 inches                 |
| Mounting Facility Quantity:                           |
| 2   |
| Terminal Location:                                    |
| Lower adjacent side two rows                          |
| Mounting Method:                                      |

**Mounting Method:** Unthreaded hole

## NSN 5905-00-951-1425

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Center To Center Distance Between Terminal Rows:                            |
|---|
| 0.100 inches  |
| Electrical Resistance Per Section:  |
| 1.000 kilohms single section  |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.300 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 175.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| 70.0/+70.0 single section   |
| Power Dissipation Rating Per Section In Watts:                              |
| 1.0 free air single section   |
| Resistance Tolerance Per Section In Percent:                                |
| 10.0/+10.0 single section   |
| Actuator Travel Control Feature:  |
| Clutch  |
| Criticality Code Justification:   |
| Zzzy  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 70.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Terminal Type And Quantity:   |
| 3 pin   |
| Reference Number Differentiating Characteristics:                           |
| Quality controlled for polaris  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A002a0  |
|   |