NSN 5905-00-951-3140

Non-wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-951-3140 **Section Quantity: Pilot Diameter:** Between 0.96830 inches and 0.96880 inches Pilot Length: 0.06200 inches **Overall Length:** Between 1.607 inches and 1.613 inches **Terminal Length:** 0.219 inches **Undercut Diameter:** Between 0.9683 inches and 0.9688 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** Between 0.391 inches and 0.453 inches **Body Length:** 1.188 inches **Overall Diameter:** 1.250 inches **Mounting Lip Diameter:** 1.06200 inches **Mounting Lip Depth:** 0.06200 inches **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 0.20 inch-ounces **Maximum Running Torque:** 0.15 inch-ounces **Shaft Runout:**

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

NSN 5905-00-951-3140

No Fiig: A002a0

Non-wire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|---|
| 5.000 percent, rated amperes c and better industrial clears |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -1.00/+1.00 2nd section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 7th secondary pattern |
| Function Conformity Per Section: |
| All sections independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 2nd section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| All sections linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 2nd section |
| Terminal Type And Quantity: |
| 6 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |