## NSN 5905-00-951-4255

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-951-4255
Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Mounting Bushing Length:
0.250 inches
Body Length:
Between 1.235 inches and 1.265 inches
Body Width:
Between 0.235 inches and 0.265 inches
Body Height:
Between 0.297 inches and 0.327 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
7.50 inch-ounces
Maximum Running Torque:
7.50 inch-ounces
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

## NSN 5905-00-951-4255

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No