## NSN 5905-00-951-4512

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-951-4512 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.0938 inches **Body Diameter:** 1.0938 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.8126 inches **Mounting Bushing Length:** 0.344 inches **Body Length:** 1.2812 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 300.0 percent, rated amperes c and better industrial clears **Rotary Actuator Travel In Angular Deg:** 300.0

**Power Dissipation Rating Per Section In Watts:** 

Any acceptable

**Resistance Tolerance Per Section In Percent:** 

-1.0/+1.0 all sections

## NSN 5905-00-951-4512

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0