AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-951-4958

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.9360 inches and 1.9370 inches

Pilot Length:

Between 0.0290 inches and 0.0320 inches

Overall Length:

Between 1.217 inches and 1.260 inches

Undercut Diameter:

Between 1.9375 inches and 1.9385 inches

Undercut Width:

Between 0.0700 inches and 0.0900 inches

Body Diameter:

Between 1.990 inches and 2.010 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.198 inches and 0.218 inches

Body Length:

Between 0.990 inches and 1.010 inches

Overall Diameter:

Between 2.099 inches and 2.151 inches

Mounting Lip Diameter:

Between 1.9900 inches and 2.0100 inches

Mounting Lip Depth:

Between 0.0680 inches and 0.0850 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 319.0 and 321.0

Maximum Starting Torque:

0.60 inch-ounces

Shaft End Play:

0.006 inches



Lateral Runout: 0.001 inches **Pilot Diameter Runout:** 0.001 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Test Data Document:** 81349-mil-r-8903 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 12 solder stud **Specification Data:** 81349-mil-r-8903 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

Fiig: