## NSN 5905-00-952-2984

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-952-2984

Electrical Resistance: 1,680 ohms Resistance Tolerance in Percent: 1,000/410.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 1,550 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1,550 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1,550 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1,550 1	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 10.0004-10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature In Deg Celsius At Full Range Of Selsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 15.0 Am	-400.0/+400.0
Resistance Tolerance in Percent: 10.000/+10.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 25.0 25.0 25.0 25.0 25.0 25.0 25.0	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/4350.0 Inclosure Method: 25.0/4350.0 Inclosure Method: 25.0/2000 Inclosure Method: 25.0/2000 Inclosure Method: 26.0/2000	0.680 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Range Of Tempuratu	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  550.0  Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  Formpurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  Inclosure Method:  Incapsulated  Forminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  20.469 inches  Body Length:  2.000 inches  Power Dissipation Rating In Watts:  4.400 free air  Style Designator:  Avial terminal each end  Fest Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  4.00 Interesting the Style Designator:  4.00 Interesting the Style Designator in the Style Designator in the Style Designator:  5.00 Interesting the Style Designator in the Style D	-10.000/+10.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  15.0/4350.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  1.469 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  1.4.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  11349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa Juit Of Measure:  Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wife lead  Reliability Indicator:  Not established  Body Diameter:  0.469 inches  Body Length:  0.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  191349-milr 26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Juit Of Measure:  Demilitarization:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.469 inches  30dy Length:  0.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  xixial terminal each end  Test Data Document:  81349-milit26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;  xixiculder commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: J. 469 inches Body Diameter: J. 469 inches Power Dissipation Rating in Watts: L4.000 free air Style Designator: Xixial terminal each end Fest Data Document: B1349-milit26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; Exceludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  John Of Measure:  Demilitarization: No	350.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.000 inches Power Dissipation Rating in Watts: 14.000 free air Style Designator: Visial terminal each end Fest Data Document: 151349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  Via Unit Of Measure: - Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.000 inches Power Dissipation Rating In Watts: 14.000 free air Skyle Designator: Natial terminal each end Fest Data Document: 181349-miliz 6/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  1/4  1/4  1/5  1/6  1/6  1/7  1/7  1/8  1/8  1/8  1/8  1/8  1/8	-55.0/+350.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.469 inches  Body Length:  0.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  181349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Va  Juit Of Measure:  - Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Rody Diameter: 0.469 inches Rody Length: 0.000 inches Power Dissipation Rating In Watts: 14.000 free air Relyle Designator: Avial terminal each end Rest Data Document: 181349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  V/a  Jinit Of Measure: - Demilitarization:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Terminal Type:
Note established  Body Diameter:  Diagony Diagony Diagony Diameter:  Diagony Diagony Diag	Wire lead
Body Length: 2.000 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure:	Reliability Indicator:
Added inches  Body Length:  2.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Not established
Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts:  14.000 free air  Style Designator: Axial terminal each end  Test Data Document:  15.1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;  25.24xial terminal each end  Test Data Document:  25.1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;  25.24xial terminal each end  Test Data Document:  26.25xial terminal each end  Test Data Document:  27.25xial terminal each end  Test Data Document:  28.25xial terminal each end  Te	0.469 inches
Power Dissipation Rating In Watts:  4.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Body Length:
Avial terminal each end  Fest Data Document:  B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	2.000 inches
Axial terminal each end  Fest Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Fest Data Document:  31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	14.000 free air
Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  No  Demilitarization:	Style Designator:
B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a  Unit Of Measure: Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a  Jnit Of Measure:  - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filg:	No
	Fiig:
A001a0	A001a0