NSN 5905-00-952-5146

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-952-5146 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 1.201 inches and 1.273 inches **Body Diameter:** Between 0.859 inches and 0.891 inches **Shaft Diameter:** Between 0.122 inches and 0.128 inches **Shaft Length:** Between 0.265 inches and 0.359 inches **Mounting Bushing Length:** Between 0.296 inches and 0.328 inches **Body Length:** Between 0.547 inches and 0.551 inches **Overall Diameter:** Between 1.031 inches and 1.095 inches **Shaft Style:** Round **Contact Arm Electrical Off Position:** Fully ccw-cw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 1080.0 and 1090.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Shaft End Play:** 0.0005 inches **Shaft Runout:** 0.002 inches **Shaft Radial Play:** 0.002 inches

Screw Thread Diameter:

0.250 inches

NSN 5905-00-952-5146

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 1080.0 and 1090.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ002a0