NSN 5905-00-953-4619

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-953-4619 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.187 inches **Body Diameter:** 1.688 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 2.375 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.781 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:**

2.0 ohms single section

Rotary Actuator Travel In Angular Deg:
300.0

NSN 5905-00-953-4619

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No