Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-953-8561

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Body Diameter:**

1.156 inches

#### Shaft Diameter:

0.128 inches

#### Shaft Length:

0.125 inches

## Mounting Bushing Length:

0.156 inches

## Body Length:

## 0.562 inches

Shaft Style:

Round, slotted

Switch Type:

Rotary

## Switch Voltage Rating In Volts:

500.0

#### Actuator Type:

Single shaft

#### **Switch Operating Position:**

Start of rotation

## Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Front end

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

1.000 megohms single section

# Power Dissipation Rating Per Section In Watts:

2.25 free air single section

# NSN 5905-00-953-8561 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent: -20.0/+20.0 single section

Switch Current Type And Rating In Amps:

0.250 ac/dc

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0