## NSN 5905-00-954-1827

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-1827 **Section Quantity:** 2 **Body Style:** Rectangular **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.063 inches **Body Length:** 2.016 inches **Body Width:** 1.078 inches **Body Height:** 0.349 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Fragility Factor:** Moderately delicate **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 1.000 percent, rated amperes c and better finish and 5.000 percent, rated amperes c and better industrial clears **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.25 7th secondary at 10'30 oclock

-20.0/+20.0 all sections

**Actuator Travel Control Feature:** 

**Resistance Tolerance Per Section In Percent:** 

Stops

## NSN 5905-00-954-1827

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
NI/a

Demilitarization:

**Unit Of Measure:** 

No

Fiig:

A002a0