## NSN 5905-00-954-1835

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-1835

Section Quantity:
3
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.031 inches
Body Length:
2.906 inches
Body Width:
0.109 inches
Body Height:
0.290 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
2.000 percent, rated amperes c and better select
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 all sections
Power Dissipation Rating Per Section In Watts:
0.25 7th secondary pattern
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 all sections
Standard Taper Curve Per Section:

A all sections

## NSN 5905-00-954-1835

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0