

View Online at <https://aerobasegroup.com/nsn/5905-00-954-2031>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**Overall Length:**

13.310 inches

**Overall Height:**

0.330 inches

**Overall Width:**

0.250 inches

**Mounting Hole Diameter:**

0.096 inches

**Shaft Diameter:**

0.130 inches

**Shaft Length:**

0.060 inches

**Body Length:**

1.250 inches

**Body Width:**

0.250 inches

**Body Height:**

0.330 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

9000.0

**Fragility Factor:**

Moderately delicate

**Lateral Distance Between Mounting Hole Centers:**

1.000 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.103 cubic inches

**Electrical Resistance Per Section:**

2.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

190.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-60.0/+60.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

150.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0