NSN 5905-00-954-2046

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-2046 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.9370 inches and 1.5620 inches Pilot Length: 0.1000 inches **Overall Length:** 2.040 inches **Undercut Diameter:** 1.437 inches **Undercut Width:** 0.0150 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.531 inches **Body Length:** 1.368 inches **Overall Diameter:** 1.812 inches **Mounting Lip Diameter:** 1.8120 inches **Mounting Lip Depth:** 0.0930 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches

Lateral Runout: 0.002 inches

NSN 5905-00-954-2046

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.001 inches
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
40.0
Mounting Facility Quantity:
4
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0