## NSN 5905-00-954-3123

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-3123

Section Quantity:				
1				
Body Style:				
Rectangular bushing mounted				
Reliability Indicator:				
Not established				
Overall Height:				
0.906 inches				
Overall Width:				
0.750 inches				
Shaft Diameter:				
0.125 inches				
Shaft Length:				
0.437 inches				
Mounting Bushing Length:				
0.375 inches				
Body Length:				
0.750 inches				
Body Width:				
0.484 inches				
Body Height:				
0.906 inches				
Shaft Style:				
Round, slotted				
Actuator Type:				
Single shaft				
Nonturn Device Location:				
At 9 oclock				
Nonturn Device Radius:				
0.234 inches				
Screw Thread Diameter:				
0.250 inches				
Screw Thread Series Designator:				
Unef				
Screw Thready Qty Per Inch (tpi):				
32.0				
Terminal Location:				
Lower adjacent side single row				
Mounting Method:				
Standard bushing				
Electrical Resistance Per Section:				
35.0 ohms single section				

## NSN 5905-00-954-3123

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation	Rating F	Per Section	In Watts:
-------------------	----------	-------------	-----------

1.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0