NSN 5905-00-954-4054

Section Quantity:

Cylindrical bushing mounted

Between 0.906 inches and 1.000 inches

Reliability Indicator:

Not established

Overall Length:

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-4054

Body Diameter:
Between 0.890 inches and 0.922 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.437 inches and 0.469 inches
Overall Diameter:
1.274 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Stop Torque:
Maximum Stop Torque: 128.00 inch-ounces
128.00 inch-ounces
128.00 inch-ounces Nonturn Device Location:
128.00 inch-ounces Nonturn Device Location: At 9 oclock
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius:
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter:
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.438 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:

NSN 5905-00-954-4054

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 251.0 and 318.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No