

View Online at <https://aerobasegroup.com/nsn/5905-00-954-4737>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.922 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.750 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.141 inches

**Shaft Style:**

Round

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

0.438 inches

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Single pole, double throw, three positions maintained

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

50.0 percent, rated amperes c and better industrial clears

**Rotary Actuator Travel In Angular Deg:**

320.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 2nd section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Switch Current Type And Rating In Amps:**

5.000 ac/dc

**Standard Taper Curve Per Section:**

F 1st section

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0