Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-5340

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.370 inches

Mounting Hole Diameter:

Between 0.081 inches and 0.091 inches

Shaft Diameter:

Between 0.172 inches and 0.204 inches

Shaft Length:

0.030 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.250 inches

Body Width:

0.312 inches

Body Height:

Between 0.355 inches and 0.365 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

Screw Thread Diameter:

0.190 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

2

Terminal Location:

Front end

Mounting Method:

Standard bushing and unthreaded hole

NSN 5905-00-954-5340

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
135.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0