NSN 5905-00-954-5340

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-5340 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.370 inches **Mounting Hole Diameter:** Between 0.081 inches and 0.091 inches **Shaft Diameter:** Between 0.172 inches and 0.204 inches **Shaft Length:** 0.030 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.250 inches **Body Width:** 0.312 inches **Body Height:** Between 0.355 inches and 0.365 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 2 **Terminal Location:** Front end

Mounting Method:

Mounting Method.

Standard bushing and unthreaded hole

NSN 5905-00-954-5340

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
135.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0