Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-954-5790

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

1.125 inches

#### Body Diameter:

1.265 inches

### Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

## Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.625 inches

## **Overall Diameter:**

1.265 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

## Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

200.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section



**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0