## NSN 5905-00-954-8669

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-954-8669

-30.0/+30.0  Electrical Resistance: 2.260 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
2.260 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established  Body Diameter: 0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document:
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length:  0.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:
Reliability Indicator: Not established  Body Diameter: 0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document:
Not established  Body Diameter:  0.187 inches  Body Length:  0.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:
Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:
0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:
Body Length:  0.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:
0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document:
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:
Style Designator:  Axial terminal each end  Test Data Document:
Axial terminal each end  Test Data Document:
Test Data Document:
81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0