

View Online at <https://aerobasegroup.com/nsn/5905-00-957-0895>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Overall Length:

2.063 inches

Body Diameter:

1.796 inches

Shaft Diameter:

0.813 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.953 inches

Body Length:

1.656 inches

Overall Diameter:

1.813 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

1.50 inch-ounces

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

300.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section absolute linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0