## NSN 5905-00-957-3213

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-957-3213

Section Quantity:

1

**Body Style:** 

Rectangular w/mounting holes/slots

**Reliability Indicator:** 

Not established

**Overall Length:** 

Between 1.280 inches and 1.344 inches

**Overall Height:** 

Between 0.770 inches and 0.844 inches

**Overall Width:** 

Between 0.270 inches and 0.290 inches

**Mounting Hole Diameter:** 

Between 0.081 inches and 0.091 inches

**Shaft Diameter:** 

Between 0.109 inches and 0.141 inches

**Shaft Length:** 

Between 0.046 inches and 0.078 inches

**Mounting Bushing Length:** 

0.250 inches

**Body Length:** 

Between 1.234 inches and 1.266 inches

**Body Width:** 

Between 0.270 inches and 0.290 inches

**Body Height:** 

Between 0.286 inches and 0.328 inches

Shaft Style:

Round, slotted

**Actuator Type:** 

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:** 

9000.0

**Maximum Starting Torque:** 

7.50 inch-ounces

**Center To Center Distance Between Terminals:** 

Between 0.672 inches and 0.704 inches

**Lateral Distance Between Mounting Hole Centers:** 

Between 0.995 inches and 1.005 inches

**Screw Thread Diameter:** 

0.216 inches

**Screw Thread Series Designator:** 

Unf

## NSN 5905-00-957-3213

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
28.0
Mounting Facility Quantity:
2
Terminal Location:
Right adjacent side single row
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
20.000 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.312 inches and 0.344 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0