

View Online at <https://aerobasegroup.com/nsn/5905-00-957-3213>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**Overall Length:**

Between 1.280 inches and 1.344 inches

**Overall Height:**

Between 0.770 inches and 0.844 inches

**Overall Width:**

Between 0.270 inches and 0.290 inches

**Mounting Hole Diameter:**

Between 0.081 inches and 0.091 inches

**Shaft Diameter:**

Between 0.109 inches and 0.141 inches

**Shaft Length:**

Between 0.046 inches and 0.078 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

Between 1.234 inches and 1.266 inches

**Body Width:**

Between 0.270 inches and 0.290 inches

**Body Height:**

Between 0.286 inches and 0.328 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

9000.0

**Maximum Starting Torque:**

7.50 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.672 inches and 0.704 inches

**Lateral Distance Between Mounting Hole Centers:**

Between 0.995 inches and 1.005 inches

**Screw Thread Diameter:**

0.216 inches

**Screw Thread Series Designator:**

Unf

**Screw Thready Qty Per Inch (tpi):**

28.0

**Mounting Facility Quantity:**

2

**Terminal Location:**

Right adjacent side single row

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

20.000 ohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

Between 0.312 inches and 0.344 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0