NSN 5905-00-957-4837

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-957-4837

Electrical Resistance: 10.000 ohms Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
10.000 ohms Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	-20.0/+20.0
Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
-3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	10.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	-3.000/+3.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	-55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Terminal Type:
Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Wire lead
Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Not established
Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Body Diameter:
0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	0.312 inches
Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Body Length:
5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	0.875 inches
Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end Shelf Life: N/a Unit Of Measure:	5.000 free air
Shelf Life: N/a Unit Of Measure:	Style Designator:
N/a Unit Of Measure:	Axial terminal each end
Unit Of Measure:	Shelf Life:
	N/a
Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0