NSN 5905-00-957-5087

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-957-5087

| Section Quantity: |
|--|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 1.313 inches |
| Body Diameter: |
| 1.531 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.625 inches |
| Mounting Bushing Length: |
| 0.500 inches |
| Body Length: |
| 0.688 inches |
| Overall Diameter: |
| 1.531 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 500.0 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 4.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |

3 tab, solder lug

NSN 5905-00-957-5087

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A002a0