## NSN 5905-00-957-9204

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-957-9204

-150.0/+150.0 Electrical Resistance: 787.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 787.000 ohms Resistance Tolerance in Percent: -1.0004-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0470.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.0003 Body Diameter: 0.0003 Body Diameter: 0.0291 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Na Unit Of Measure:	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0903 Body Diameter: 0.0903 Body Diameter: 0.0909 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: Via Unit Of Measure:	
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/47.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.0900 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: Na Unit Of Measure: Demilitarization: No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/470.0  Inclosure Method:  Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.0003  Body Diameter:  0.0901 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.128 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Na  Unit Of Measure:  — Demilitarization:  No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.0909 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial teminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: — Demilitarization: No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0  Inclosure Method: Hermatically sealed  Terminal Type: Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.0003  Body Diameter: 0.0003  Body Diameter: 0.090 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Oata Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.5.0470.0 Inciosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.0003 Body Diameter: 0.0903 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Avial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure: Demilitarization: No	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.090 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	
-5.0/+70.0 Inclosure Method: Hormetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.0003 Body Diameter: 0.090 Inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.090 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.090 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	-55.0/+70.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.090 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.090 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Hermetically sealed
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.090 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type:
Established  Reliability Failure Rate Level In Percent:  0.0003  Body Diameter:  0.090 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Wire lead
Reliability Failure Rate Level In Percent:  0.0003  Body Diameter:  0.090 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Reliability Indicator:
Body Diameter:  0.090 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Established
Body Diameter:  0.090 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Reliability Failure Rate Level In Percent:
0.090 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	0.0003
Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Body Diameter:
Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.090 inches
Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Body Length:
O.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	0.281 inches
Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Power Dissipation Rating In Watts:
Test  Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	0.125 free air
Style Designator:  Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Criticality Code Justification:
Axial terminal each end  Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Test
Test Data Document:  11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Style Designator:
11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	11293-35-267419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life:  N/a Unit Of Measure:  Demilitarization:  No	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization:  No	N/a
No	Unit Of Measure:
No	<del></del>
No	Demilitarization:
· ··ʊ·	Fiig: