Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-958-3264

## Section Quantity:

1

# Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.876 inches

#### **Body Diameter:**

1.047 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.625 inches

## Mounting Bushing Length:

## 0.500 inches

**Body Length:** 

1.063 inches

#### **Overall Diameter:**

1.047 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Stop Torque:

80.00 inch-ounces

## Nonturn Device Location:

At 6 oclock

#### Nonturn Device Radius:

0.250 inches

#### Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Rear end

## Mounting Method:

Locking bushing

# NSN 5905-00-958-3264

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



#### Electrical Resistance Per Section:

50.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

Between 290.0 and 305.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

**Power Dissipation Rating Per Section In Watts:** 

6.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

#### **Actuator Travel Control Feature:**

#### Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

**Standard Taper Curve Per Section:** 

A single section

#### **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 tab, solder lug

Specification Data:

81349-mil-r-22/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0