## NSN 5905-00-958-3971

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-958-3971

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Terminal Length:
Between 0.172 inches and 0.202 inches
Mounting Hole Diameter:
Between 0.075 inches and 0.081 inches
Shaft Diameter:
0.083 inches
Shaft Length:
0.030 inches
Body Length:
0.500 inches
Body Width:
0.220 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
5.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

## NSN 5905-00-958-3971

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0