NSN 5905-00-958-9256

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-958-9256

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Thread Length:
0.300 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.093 inches
Shaft Length:
0.938 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
0.320 inches
Shaft Style:
Round, threaded
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
4.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:

0.8 free air single section

NSN 5905-00-958-9256

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fixed Tap Quantity Per Section:	
1 single section	
Resistance Tolerance Per Section In Percent:	
5.0/+5.0 single section	
Actuator Travel Control Feature:	
Stops	
Tap Location From Ccw Terminal Per Section In Ohms:	
2000.0 single section	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Special Features:	
Push pull actuated shaft, shaft when in retracted position extends through opposite end 0.440 in.	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
A002a0	