## NSN 5905-00-959-1508

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-959-1508

Electrical Resistance: 5.760 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Tost Data Document: 07482-4983-45761b drawling (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, shelf Life: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-1983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	-50.0/+50.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing, shelf Life: N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wive lead Reliability Indicator: Not established Body Diameter: -0.135 inches Body Length: -0.406 inches Power Dissipation Rating In Watts: -0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-983-5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	5.760 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-7983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-4983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.135 inches  Body Length:  0.406 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  07482-7983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-9883+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-7983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-1983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	175.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-7983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+175.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.135 inches  Body Length: 0.406 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.135 inches  Body Length: 0.406 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end  Test Data Document: 07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Encapsulated
Reliability Indicator:  Not established  Body Diameter: 0.135 inches  Body Length: 0.406 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end  Test Data Document: 07482-7983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Terminal Type:
Note established  Body Diameter:  0.135 inches  Body Length: 0.406 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end  Test Data Document: 07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Wire lead
Body Diameter:  0.135 inches  Body Length: 0.406 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end  Test Data Document: 07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Reliability Indicator:
Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Length:  0.406 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Body Diameter:
0.406 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end  Test Data Document: 07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	0.135 inches
Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  0.7482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Body Length:
O.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  O7482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.406 inches
Style Designator: Axial terminal each end Test Data Document: 07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.125 free air
Test Data Document:  07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	07482-r983+5761b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
N/a Unit Of Measure: Demilitarization: No Filig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0