NSN 5905-00-959-1731

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-959-1731

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
0.640 inches
Shaft Diameter:
0.125 inches
Shaft Length:
1.750 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.421 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.234 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Standard Taper Curve Per Section:
F single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5905-00-959-1731

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0