NSN 5905-00-959-2795

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-959-2795

Section Quantity:
1
Reliability Indicator:
Not established
Overall Length:
1.325 inches
Shaft Diameter:
0.125 inches
Mounting Bushing Length:
0.300 inches
Overall Diameter:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
16200.0
Maximum Starting Torque:
1.30 inch-ounces
Maximum Running Torque:
0.75 inch-ounces
Screw Thread Diameter:
0.216 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
28.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section

NSN 5905-00-959-2795

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Special Features:
Screwdriver tunable flush slotted shaft
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No