

View Online at <https://aerobasegroup.com/nsn/5905-00-959-3416>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.485 mils and 0.515 centimeters

Shaft Diameter:

Between 0.0932 inches and 0.0935 inches

Shaft Length:

Between 0.656 inches and 0.718 inches

Mounting Bushing Length:

Between 0.266 inches and 0.296 inches

Body Length:

Between 0.985 inches and 1.000 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.80 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Maximum Stop Torque:

20.00 inch-ounces

Shaft End Play:

0.010 inches

Shaft Runout:

0.003 inches

Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.003 inches

Shaft Radial Play:

0.003 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.30/+0.30 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary quality

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

7 oclock all primaries

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0