## NSN 5905-00-959-8998

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-959-8998 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.530 inches **Terminal Length:** Between 0.172 inches and 0.202 inches **Overall Height:** 0.500 inches **Overall Width:** 0.407 inches **Mounting Hole Diameter:** Between 0.075 inches and 0.081 inches **Shaft Diameter:** 0.083 inches **Shaft Length:** 0.030 inches **Body Length:** 0.500 inches **Body Width:** 0.220 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity: Terminal Location:** 

Right adjacent side single row

**Mounting Method:** 

Unthreaded hole

**Center To Center Distance Between Terminal Rows:** 

0.100 inches

## NSN 5905-00-959-8998

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical	Resistance	Per	Section:

1.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0