NSN 5905-00-962-2887

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-962-2887 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.750 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 60.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

NSN 5905-00-962-2887

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -25.0/+25.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Resistance Tolerance Per Section In Percent:** -2.0/+2.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**