## NSN 5905-00-963-1260

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-963-1260

Ocation Oceantity
Section Quantity:
3
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
1.750 inches
Flat Height:
0.344 inches
Body Diameter:
1.700 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Body Length:
1.800 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
8.0 ohms c and better select
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
500.0 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections

## NSN 5905-00-963-1260

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0