Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-963-1345

Section Quantity:

3

Body Style: Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.9683 inches and 0.9688 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.970 inches

Undercut Width:

0.0600 inches

Body Diameter:

1.099 inches

Shaft Diameter:

0.120 inches

Shaft Length:

0.469 inches

Body Length:

1.630 inches

Mounting Lip Diameter:

Between 1.0570 inches and 1.0650 inches

Mounting Lip Depth:

0.0600 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Shaft End Play:

0.003 inches

Shaft Runout:

0.001 inches



Lateral Runout: 0.001 inches **Pilot Diameter Runout:** 0.001 inches **Shaft Radial Play:** 0.0006 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 6.0 percent, rated amperes c and better industrial clears **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -200.0/+200.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.9 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 all sections **Actuator Travel Control Feature:** Clutch **Function Characteristic Per Section:** All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 all sections Unpackaged Unit Weight: 5.0 grams **Terminal Type And Quantity:** 9 tab, solder lug Shelf Life: N/a Unit Of Measure:



Demilitarization:

No

Fiig:

A002a0