NSN 5905-00-963-3959

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-963-3959

Continu Countifus
Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.250 inches
Body Width:
0.938 inches
Body Height:
0.719 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, double throw, three positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:

Standard bushing

NSN 5905-00-963-3959

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Switch
Electrical Resistance Per Section:
3.0 megohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
3.000 ac
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4002a0