NSN 5905-00-964-0497

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-964-0497

| -20.0/+20.0 Electrical Resistance: 60.000 ohms Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Teminal Type: Wire lead Reliability Indicator: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| +25.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| Hermetically sealed Terminal Type: Wire lead Reliability Indicator: |
| Terminal Type: Wire lead Reliability Indicator: |
| Wire lead Reliability Indicator: |
| Reliability Indicator: |
| |
| Not established |
| |
| Body Diameter: |
| 0.312 inches |
| Body Length: |
| 1.375 inches |
| Power Dissipation Rating In Watts: |
| 7.000 free air |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 49956-280mr128 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |
| |