NSN 5905-00-964-2287

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-964-2287 **Section Quantity: Reliability Indicator:** Not established First Flat Length: 0.343 inches Flat Height: 0.219 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.781 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 24.0 **Mounting Facility Quantity: Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 1.500 percent, rated amperes c and better industrial clears **Power Dissipation Rating Per Section In Watts:** 25.0 free air single section **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections **Standard Taper Curve Per Section:** A single section **Special Features:** Mtg holes spaced 0.813 inch c to c **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

NSN 5905-00-964-2287

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A002a0