NSN 5905-00-964-4419

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-964-4419 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 1.448 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Body Length:** 1.573 inches **Overall Diameter:** 1.000 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 2282.0 **Maximum Starting Torque:** 0.40 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

NSN 5905-00-964-4419

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.00300 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
2282.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0