## NSN 5905-00-964-4423

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-964-4423

Section Quantity:
1
Reliability Indicator:
Not established
Overall Length:
1.448 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.250 inches
Overall Diameter:
0.875 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.000 kilohms single section
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section

## NSN 5905-00-964-4423

Precision Wire Wound Variable Resistor - Page 2 of 2



	Tap	Location	<b>Tolerance</b>	Per	Section:
--	-----	----------	------------------	-----	----------

-4.0/+4.0 degrees angular rotation single section

**Resistance Tolerance Per Section In Percent:** 

-3.0/+3.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Terminal Type And Quantity:** 

4 tab, solder lug

.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0