NSN 5905-00-964-6553

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-964-6553 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 1.780 inches **Terminal Length:** 1.500 inches **Body Diameter:** 0.345 inches **Body Length:** 0.280 inches **Body Height:** 0.345 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 20.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion

NSN 5905-00-964-6553

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature C	oefficient Of	Resistance	Wire Per	Section In	Ppm Per	Deg Ce	elsius:
						5	

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0