

View Online at https://aerobasegroup.com/nsn/5905-00-964-7368

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

# **Body Diameter:**

1.825 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.750 inches

### **Body Length:**

2.560 inches

### Shaft Style:

# Round, slotted

# Shaft Bearing Type:

Ball

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

### Maximum Starting Torque:

2.00 inch-ounces

### Maximum Running Torque:

2.00 inch-ounces

### Maximum Stop Torque:

480.00 inch-ounces

### Shaft End Play:

0.005 inches

#### Shaft Runout:

0.001 inches

#### **Pilot Diameter Runout:**

0.001 inches

#### Shaft Radial Play:

0.001 inches

## **Terminal Location:**

Longitudinally positioned on the circumference

## **Mounting Method:**

Clamp ring

## **Electrical Resistance Per Section:**

33.333 kilohms all sections

# NSN 5905-00-964-7368

Precision Wire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** 3780.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 2nd section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -25.0/+25.0 all sections **Power Dissipation Rating Per Section In Watts:** 5.0 free air all sections **Function Conformity Per Section:** All sections absolute linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -0.0/+0.0 degrees angular rotation single section **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 all sections **Actuator Travel Control Feature:** Stops Tap Location From Ccw Terminal Per Section In Ohms: 16666.5 single section **Function Characteristic Per Section:** All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 all sections **Special Features:** Two section variable resistor in one unit, section one is not tapped and section two is **Test Data Document:** 06481-900217-18 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 7 turret Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0